

# PROTECTAPEEL

PAINT • PROTECT • PEEL

## Anti - Rust

**Protectapeel Anti-Rust** is a weather resistant, peelable protective coating that has been formulated with a special inhibitor to protect steel surfaces from rust, weathering and surface damage such as scratches, spillage and dust. **DO NOT USE ON ACRYLIC SURFACES.**

**Colour** - Blue. Also available in clear or pigmented in different colours upon request.

**Health & Safety** - The compound is non toxic and non flammable in the wet state. The dry film waste may be disposed of as low hazard. Please see separate Health & Safety Sheet.

**Application** - **By Lambswool Roller** – Apply 2 coats, allowing 1st to tack off. Apply generously to achieve a **min wet film thickness (WFT) of 250 Microns (100 Microns DFT)**

**By Spray** –Apply with airless spray gun, using a 17 thou tip size and a box coat to achieve a **min wet film thickness (WFT) of 250 Microns (100 Microns DFT)**. To avoid “feather edges”, apply masking tape before the product is applied. Paint up to and over the masking tape edge then remove tape when product is still wet to leave a defined edge.

**A minimum wet film thickness of 250 microns (100 micron dry film thickness) must be achieved, anything less may result in the product becoming difficult to remove.** Do not apply in wet or freezing conditions and protect from rainfall.

The contents of the containers should be mixed thoroughly before use.

**Repair** - If the protective coating rips, repair by lifting the ripped patch and apply a fresh coat to the underside and reseal. Alternatively, cut away the damaged area and apply a fresh coat.

**Drying Time** - A WFT of 250 microns will be tack free in approximately 2 hours at room temperature. Force drying may be used by increasing the surface temperature to a maximum of 50°C and using moving air.

**Surfaces** - Steel.



**Coverage** - One kilo/litre will cover approximately 5m<sup>2</sup> at a WFT of 250 microns.

**Removal** - The dry film can be easily removed either by hand peeling or by pressure hose. Do not remove in freezing conditions as the coating may be brittle.

**External Weather Resistance** - Anti-Rust is suitable for **up to 12 months exposure**.

**Storage** - Shelf life 12 months. Store at temperatures between 5°C - 25°C. **DO NOT ALLOW LIQUID TO FREEZE.**

**Clean Down** - Clean rollers and equipment with water immediately after use.

**General Note:** It is important that this product is thoroughly evaluated under production conditions before being commercially adopted (Such an evaluation should incorporate a reference to ageing). The above recommendations are made in good faith for the guidance of users and are without liability. Any queries should be referred to our Technical Sales Department.